

6 V 225 Ah (C₂₀) Deep Cycle Flooded Battery

PHYSICAL CHARACTERISTICS

	SI Units	US Units
Length	261 mm	10,28 inch
Width	181 mm	7,13 inch
Height	276 mm	10,87 inch
Typical weight	29,13 kg	64,22 lbs



Specifications:

- Nominal voltage: 6 V
- Rated capacity: 225 Ah (at C₂₀ and 25 °C)
- Plate technology: Antimony / Antimony
- Separator: Polyethylene
- Electrolyte: Sulphuric acid; analytical grade
- Standards: IEC 60254; IEC 61427
- Case / Lid material: Polypropylene
- Lid type: Flat
- Terminal type: Bolted
- Carrying Handles: Available
- Cycles at 75% DoD: up to 1000 cycles
- PVES applications: up to 2000 cycles

Performance characteristics:


BATTERY DISCHARGE PERFORMANCE AT 25°C

Discharge rate	C ₅ (5 h)		C ₂₀ (20 h)	C ₁₀₀ (100 h)	Capacity at 25 A		
End of discharge voltage	5,10 V		5,25 V	5,40 V	5,25 V		
Discharge capacity	185 Ah		225 Ah	248 Ah	450 min / 188 Ah		
Temperature correction factor of discharge C ₅ (5 h) capacity							
Temperature	-10 °C	0 °C	10 °C	15 °C	20 °C	30 °C	40 °C
Correction factor	0.83	0.87	0.92	0.94	0.97	1.03	1.09


BATTERY CHARGE CONDITIONS

Charging profiles: WaW0 and IUla Charge factor: 1.10 – 1.20


WaW0 – (double slope taper) characteristics for flooded batteries




IUla – characteristics for flooded batteries



Charging times with WaW0-characteristics in hours



Charging times with IUla-characteristics in hours



It is mandatory to check the electrolyte level every 3 months and top up with deionized water to the markings.